

MATERIAL SAFETY DATA SHEET

THE HALLSTAR COMPANY

Section 1 - Identification of Substance and Company

Product Name: PLASTHALL® 203 LP

Product Code: 1506

Chemical Name: Dibutoxyethyl Adipate

Supplier: The HallStar Company⁽¹⁾
120 S. Riverside Plaza Suite 1620
Chicago, IL 60606 PH: 877-427-4255
USA

HMIS
Health: 1
Flammability: 1
Reactivity: 0
Gloves & Safety Glasses

Emergency Phone Numbers: The HallStar Company (708)594-5999
CHEMTREC (transportation) (800)424-9300

Section 2 - Information on Ingredients

<u>Chemical Name</u>	<u>CAS #</u>
Dibutoxyethyl Adipate	141-18-4

Section 313 Supplier Notification: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

<u>Chemical Name</u>	<u>CAS #</u>	<u>Percent by Weight</u>
Glycol Ether Compounds	*	100

Section 3 - Hazard Identification

Clear liquid, mild odor.

Potential Health Effects

Skin Contact: Repeated or prolonged skin contact may cause skin irritation.
Eye Contact: May cause slight eye irritation of susceptible persons.
Ingestion: Substance may be harmful if swallowed. May irritate mouth, throat and stomach.
Inhalation: May cause dizziness.

Section 4 - First Aid Measures

Skin Contact: Wash affected skin with soap and water. Seek medical attention if symptoms persist.
Eye Contact: Flush eyes with large amounts of water for at least 15 minutes. If irritation persists, consult a physician.
Ingestion: Seek medical advice.
Inhalation: Person should be moved to a fresh air environment.

Section 5 - Explosion and Fire-Fighting Measures

Extinguishing Media: CO₂, Dry Chemical, Water Fog

Special Fire-Fighting Procedures: A MSHA/NIOSH approved self-contained breathing apparatus should be worn. Use water spray to cool fire-exposed containers.

Unusual Fire and Explosion Hazards: Solid streams of water directed at burning liquid may cause frothing.

Section 6 - Accidental Release/Spill Procedures

Steps to be Taken in Case Material is Released or Spilled: Dike and contain the spill with inert material (i.e., sand, earth, sawdust) and transfer liquid and solid diking material to separate containers for recovery or disposal. Wash floor area with hot water solution. Remove contaminated clothing and wash before reuse. Wash affected skin areas with soap and water. Keep spills out of all sewers and bodies of water.

Section 7 - Handling and Storage

Any use of this product in an elevated temperature process should be evaluated to establish and maintain safe operating procedures.

Containers should be kept tightly closed and stored in a dry well-ventilated place

Section 8 - Personal Protection

OSHA Permissible Exposure Limit (PEL): None established

Hand Protection: Impervious

Eye Protection: Safety glasses

Respiratory Protection: None required for normal operations.

Engineering Measures: For normal operation, local exhaust ventilation should suffice. Direct exhaust when material becomes heated and vapors are given off.

Other: Impervious apron and eyewash facility.

Section 9 - Physical and Chemical Properties

Boiling Point:	>500	Specific Gravity:	0.9955
Flash Point (COC):	350°F	Evaporation Rate:	Nil
Vapor Density (Air=1):	N/A	Solubility in Water:	0.08%
Vapor Pressure (68°F):	0.071	pH:	N/A
Appearance and Odor:	Clear liquid, mild odor.		

Section 10 - Stability and Reactivity

Stability: This product is stable under normal conditions.

Conditions to Avoid: N/A

Hazardous Polymerization: Will not occur under normal circumstances.

Section 11 - Toxicological Information

No information is available at this time.

Section 12 - Ecological Information

This product does not contain any ozone depleting compounds (ODC's).

Section 13 - Disposal Considerations

Waste Disposal Methods: Material should be disposed of in accordance to current local and national regulations. Contacting a waste disposal service is recommended.

Section 14 - Transport Information

Not classified as hazardous according to the Department of Transportation.

Section 15 - Regulatory Information

Toxic Substances Control Act (TSCA): This product is in compliance with the TSCA regulation of the United States.
European Inventory of Existing Chemical Substances (EINECS): This product is listed on the EINECS inventory of Europe. Registration#: 205-465-5

Superfund Amendments and Reauthorization Act (SARA): This product has the following hazards as defined in Section 311/312 of 40 CFR Part 372:

Hazards
None

This product contains the following chemicals subject to the reporting requirements of Section 313 or Title III of SARA and 40 CFR Part 372:

Ingredients
Glycol Ether Compounds

California Proposition 65: This product does not contain substances known to the State of California to cause cancer, birth defects, or other reproductive harm per the Safe Drinking Water and Toxic Enforcement Act of 1986:

Section 16 - Other Information

Prepared By: DCU

Revision Date: 05/11
Supersedes: 06/07

All information is presented in good faith using available information. The HallStar Company makes no representation of the accuracy or completeness of the information. The user should consider this information as a supplement to other information that may be available. User should also determine suitability of information in their situation to determine proper use and disposal, protection of persons and the environment.

⁽¹⁾ Affiliated companies include RTD*HallStar Company, HallStar Solutions Corp., Ester Solutions Company, Memphis Solutions Company and Marine Magnesium & Minerals Company.