

MATERIAL SAFETY DATA SHEET

THE HALLSTAR COMPANY

Section 1 - Identification of Substance and Company

Product Name: SUPRMIX[®] PARA-Flux 022

Product Code: 4796

Chemical Name: Hydrated Amorphous Silica and Asphalt Compound

Supplier: The HallStar Company ⁽¹⁾
120 S. Riverside Plaza Suite 1620
Chicago, IL 60606 PH: (877) 427-4255
USA

HMIS

Health: 1
Flammability: 1
Reactivity: 0
Gloves, Safety Glasses &
Dust Mask

Emergency Phone Numbers: The HallStar Company: (708) 594 - 5999
CHEMTREC: (800) 424 - 9300

Section 2 - Information on Ingredients

<u>Chemical Name</u>	<u>CAS#</u>
Asphalt	8052-42-4
Petroleum Oil	64741-95-3
Refined Petroleum Wax	64742-61-6
Hydrated Amorphous Silica	7631-86-9

Section 3 - Hazard Identification

Appearance/Odor: Dark Brown to Black Strong Asphalt Odor Powder

Potential Health Effects

Skin Contact: Repeated or prolonged skin contact may cause skin irritation.

Eye Contact: May cause slight eye irritation of susceptible persons.

Ingestion: Substance may be harmful if swallowed. May irritate mouth, throat and stomach.

Inhalation: May cause dizziness.

Section 4 - First Aid Measures

Skin Contact: Wash affected skin with soap and water. Seek medical attention if symptoms persist.

Eye Contact: Flush eyes with large amounts of water for at least 15 minutes. If irritation persists, consult a physician.

Ingestion: Seek medical advice.

Inhalation: Person should be moved to a fresh air environment.

Section 5 - Explosion and Fire-Fighting Measures

Extinguishing Media: CO₂, Dry Chemical, Water Fog

Special Fire-Fighting Procedures: A MSHA/NIOSH approved self-contained breathing apparatus should be worn.

Unusual Fire and Explosion Hazards: This material will burn vigorously when exposed to a flame at elevated temperatures.

Section 6 - Accidental Release/Spill Procedures

Steps to be Taken in Case Material is Released or Spilled: Contain the spill and transfer to containers for recovery or disposal. Wash floor area with hot water solution. Remove contaminated clothing and wash before reuse. Wash affected skin areas with soap and water. Keep spills out of all sewers and bodies of water.

Section 7 - Handling and Storage

Any use of this product in an elevated process, should be evaluated to establish and maintain safe operating procedures.

Keep from contact with oxidizing materials. Avoid open flames and excessive heat.

Containers should be kept tightly closed and stored in a dry well-ventilated place.

Section 8 - Personal Protection

- Exposure Limits:** OSHA 8-hour Time Weighted Average (TWA) = 6 mg/m³ (total dust)
ACGIH Threshold Limit Value (TLV) = 5 mg/m³ (asphalt fumes from heating)
- Hand Protection:** Impervious gloves
- Respiratory Protection:** Dust mask is recommended. Use NIOSH approved respirator with particulate prefilter, when dusting is above the TWA or an appropriate cartridge when the asphalt fumes are above the TLV.
- Eye Protection:** Safety glasses
- Engineering Measures:** For normal operation, local exhaust ventilation should suffice. Direct exhaust when dusting becomes a nuisance.
- Other:** Eyewash facility in vicinity.

Section 9 - Physical and Chemical Properties

Boiling Point:	N/A	Bulk Density:	100g / 174 ml.
Flash Point:	N/A	Evaporation Rate:	Negligible
Vapor Density (Air=1):	N/A	Solubility in Water:	Insoluble
% Active:	72		

Appearance and Odor: Dark Brown to Black Strong Asphalt Odor Powder

Section 10 - Stability and Reactivity

Stability: This product is stable under normal conditions.

Conditions to Avoid: Strong oxidizing agents.

Hazardous Polymerization: Will not occur under normal circumstances.

Section 11 - Toxicological Information

No information is available at this time.

Section 12 - Ecological Information

This product does not contain any ozone depleting compounds (ODC's).

Section 13 - Disposal Considerations

Waste Disposal Methods: Material should be disposed of in accordance to current local and national regulations. Contacting a waste disposal service is recommended.

Section 14 - Transport Information

Not classified as hazardous according to the Department of Transportation.

Section 15 - Regulatory Information

Toxic Substances Control Act (TSCA): This product is in compliance with the TSCA regulation of the United States.

Superfund Amendments and Reauthorization Act (SARA): This product has the following hazards as defined in Section 311/312 of 40 CFR Part 372:

Hazards

Immediate Health Hazard

This product contains the following chemicals subject to the reporting requirements of Section 313 or Title III of SARA and 40 CFR Part 372:

Ingredients

None

California Proposition 65: This product contains the following substances known to the State of California to cause cancer, birth defects, or other reproductive harm per the Safe Drinking Water and Toxic Enforcement Act of 1986:

Ingredients

None

Section 16 - Other Information

Prepared By: AAC

Revision Date: 06/07

Supersedes: 01/05

All information is presented in good faith using available information. The HallStar Company makes no representation of the accuracy or completeness of the information. The user should consider this information as a supplement to other information that may be available. User should also determine suitability of information in their situation to determine proper use and disposal, protection of persons and the environment.

⁽¹⁾ Affiliated companies include RTD*HallStar Company, HallStar Solutions Corp., Ester Solutions Company, Memphis Solutions Company and Marine Magnesium & Minerals Company.